


White Grease



MATERIAL SAFETY DATA SHEET

Section I - Identification

Manufacturer AGS Company(American Grease Stick Co.)
2651 Hoyt Street Phone: 800-253-0403
Muskegon Hts., MI 49444



NFPA

Trade Name LITH-EASE (Cat. Nos. WL-1, 8, 14, 15, 19, 35, 55)

Common Name White Grease Chemical Family Mixture

Section II - Hazardous Ingredients

Hazardous Ingredient	CAS No.	Wgt. %	TLV
1. <u>White Lithium Grease</u>	<u>Not Assigned</u>	<u>100%</u>	<u>5 mg/m³ (oil)</u>
2. _____	_____	_____	_____
3. _____	_____	_____	_____
4. _____	_____	_____	_____
5. _____	_____	_____	_____
6. _____	_____	_____	_____
7. _____	_____	_____	_____
8. _____	_____	_____	_____
9. _____	_____	_____	_____
10. _____	_____	_____	_____
11. _____	_____	_____	_____
12. _____	_____	_____	_____

Section III - Physical Data

Ph as Supplied Not Applicable Boiling Point Not Determined
Ph - Diluted Not Applicable % Volatiles Not Applicable
Water Solubility Nil Vapor Press Not Applicable
Specific Grav. (H₂O=1) 0.90 Vapor Density Not Applicable
Melt Point 360°F. (min.) ASTM D2265 Evap. Rate Not Applicable
Appearance Pale yellow semi-solid with mineral oil odor.

Original Issue Date 11/12/85
Revision No. 1 Date 01/23/89

29

920910 9T1dW

Product - LITH-EASE

(Cat. Nos. WL-1, 8, 14, 15
19, 35, 55)

Section IV - Fire & Explosion Data

Flash Pt. > 400°F. Method C.O.C.

Auto Ignition Temp. Not Determined

Flammable Limits LEL Not Determined UEL Not Determined

Extinguishing Media Dry chemical, CO₂, foam, water fog, sand and earth.

Special Procedures Wear self-contained breathing apparatus.

Unusual Hazards Dense smoke.

Section V - Reactivity Data

Unstable Conditions and Auto Reactive Stable

Incompatible Materials Strong oxidizing agents.

Hazardous Decomposition Products CO and CO₂

Section VI - Emergency First Aid

Eyes Flush with water for at least 15 minutes. Call a physician immediately.

Skin Wash thoroughly with soap and water.

Ingestion Do not induce vomiting. Call a physician immediately.

Inhalation Of oil mist from grease--remove victim to fresh air. Administer oxygen or artificial respiration as required. Consult a physician.

Original Issue Date 11/12/85
Revision No. 1 Date 01/23/89

Product - LITH-EASE
(Cat. Nos. WL-1, 8, 14, 15
19, 35, 55)

Section VII - Health Effects

Eyes May cause irritation.

Skin May cause irritation on prolonged or repeated contact.

Inhalation When at elevated temperature or aerosolized, may cause irritation
of the respiratory tract.

Ingestion Contains petroleums, may cause diarrhea and nausea.

Other Effects Not known.

Section VIII - Ventilation and Protective Measures

Ventilation Requirements General exhaust exceptable where a TLV of 5 mg/m^3
as mineral oil will not be exceeded.

Protective Equipment

Respiratory None required with adequate ventilation.

Eyes Safety glasses.

Gloves Rubber or plastic oil resistant.

Other Eye wash in work area.

Original Issue Date 11/12/85
Revision No. 1 Date 01/23/89

Product - LITH-EASE

(Cat. Nos. WL-1, 8, 14, 15
19, 35, 55)

Section IX - Storage and Handling Procedures

Conditions to Avoid None listed.

Other Precautions Keep containers closed.

Section X - Spill Procedures and Waste Disposal

Accidental Release or Spill Procedures Transfer bulk of material to a container.

Remove the residue with an absorbant material.

Waste Disposal Method Not known.

Special Restrictions on Waste Disposal Removal by an approved, licensed,
waste hauler.

Approved By 
Tommy Jones, Manager Technical Resources

Original Issue Date 11/12/85

Revision No. 1 Date 01/23/89

The Information Herein Is Given In Good Faith, But No Warranty,
Expressed Or Implied, Is Made.