

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

3270

DATE OF PREP. 6-29-76

Section I

Discontinued

MANUFACTURER'S NAME Rust-Oleum Corporation

STREET ADDRESS 2301 Oakton Street

CITY, STATE, AND ZIP CODE Evanston, Illinois 60202

EMERGENCY TELEPHONE NO. (312) 869-1100

PRODUCT CLASS Aerosol

MANUFACTURERS CODE IDENTIFICATION 4277

TRADE NAME Barbecue Copper Bronze

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE
		PPM	mg/M ³		
Toluene	28.8	200		1.2	
Xylol	18.8	200		1.0	
N-Butyl Alcohol	0.5	100		1.45	
Propellant - (propane - isobutane)	25	1000		2.4	
Aerosol - Contents under pressure					

Section III - PHYSICAL DATA

BOILING RANGE Propellant below 0°F.

VAPOR DENSITY HEAVIER LIGHTER THAN AIR

EVAPORATION RATE FASTER SLOWER THAN ETHER

PERCENT VOLATILE BY VOLUME NA

WEIGHT PER GALLON NA

Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY³ Flammable Compressed Gas
No Label Required

FLASH POINT Propellant Below 0°F.
(TOC)

LEL See II

EXTINGUISHING MEDIA Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical or foam) designed to extinguish NFPA Class 1B liquid fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Do not spray near open flame. Keep at room temperature as exposure to direct sunlight or other heat may cause bursting.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE See Section II

EFFECTS OF OVEREXPOSURE Inhalation: Anesthetic. Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma.

Skin or Eye Contact: Primary irritation.

EMERGENCY AND FIRST AID PROCEDURES Fumes: Remove from exposure. Restore breathing. Keep warm and quiet. Notify a physician. Spray (eyes): Flush immediately with copious quantities of running water for at least 15 minutes. Take to a physician for definitive medical treatment.

Section VI – REACTIVITY DATA

STABILITY UNSTABLE STABLE

CONDITIONS TO AVOID

INCOMPATIBILITY (Materials to avoid) NA

HAZARDOUS DECOMPOSITION PRODUCTS By Open Flame - Carbon Monoxide, Carbon Dioxide

HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR

CONDITIONS TO AVOID Do not store above 120° F.

Section VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Remove all sources of ignition (flames, hot surfaces, and electrical, static, or frictional sparks.) Avoid breathing vapors. Ventilate area. Remove with inert absorbent and non-sparking tools.

WASTE DISPOSAL METHOD Dispose of in accordance with local, state, and federal regulations. Do not incinerate

Section VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION

In outdoor or open areas use Bureau of Mines approved mechanical filter respirator to remove solid air borne particles of overspray during spray application. In restricted ventilation areas use Bureau of Mines approved chemical-mechanical filters designed to remove a combination of particulate and gas and vapor. In confined areas use Bureau of Mines approved air line type respirators or hoods.

VENTILATION Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV of most hazardous ingredient in SECTION II below acceptable limit, LEL in SECTION IV below stated limit

PROTECTIVE GLOVES

EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

Section IX – SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not store above 120° F. Store large quantities in buildings designed and protected for storage of NFPA Class II flammable (or combustible) liquids.

OTHER PRECAUTIONS

Do not puncture or incinerate. Do not spray near fire or open flame. Keep away from children.