

MATERIAL SAFETY DATA SHEET: DROP DEAD II AEROSOL

Section I - General Information

(000000-000000- - 5414)

Date of Issue:

9/26/2006 12:00:00 AM

Supersedes:

2/12/2001 12:00:00 AM

Chemical Name & Synonyms:

N/A

Trade Name & Synonyms:

DROP DEAD II AEROSOL

Chemical Family:

AQUEOUS PERMETHRIN SOLUTION

Formula is a mixture: [N]

Manufacturer Name:

CHEMSEARCH DIV. OF NCH CORP.

Manufacturer Address:

BOX 152170
IRVING, TX 75015

Prepared By:

M McDowell/Chemist

Product Code Number:

5414

Emergency Phone Number:

800-424-9300

Section II - Hazardous Ingredients

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

<u>Chemical Name (Ingredients)</u>	<u>Hazard</u>	<u>TLV</u>	<u>PEL</u>	<u>STEL</u>	<u>CAS #</u>
SYNTHETIC ISOPARAFFINIC HYDROCARBON	IRRITANT	5 MG/M3\$ 1	5 MG/M3\$ 2	10 MG/M3\$1	64742-47-8
PROPANE	ASPHYX	1000 PPM#1	1000 PPM 2	N/E	74-98-6
ISOBUTANE	ASPHYX	1000 PPM#1	N/E 2	N/E	75-28-5
\$ OIL MIST VALUES					
# ALIPHATIC HYDROCARBON GASES					

Section III - Physical Data

Boiling Point (°F): 212°	Specific Gravity (H₂O=1): 0.85
Vapor Pressure (mm Hg): 25.6	Color: WHITE
Vapor Density (Air=1): 0.9	Odor: MILD PETROLEUM
pH @ 100% : 6.0	Clarity: OPAQUE
% Volatile by Volume: 93	Evaporation Rate (BuAc=1): 1.2
H₂O Solubility: COMPLETE	Viscosity: SLIGHT VISCOUS

Section IV - Fire and Explosion Hazard

Flash Point: >200°F
Flammable Limits: PROPANE/ISOBUTANE
LEL: 0.5%

Method Used: SETAFLASH
UEL: 9.5%
Aerosol Level (NFPA 30B): 1

Extinguishing Media:

☒ Foam	☒ Alcohol Foam	☒ CO2
☒ Dry Chemical	☒ Water Spray	☐ Other

NFPA 704 Hazard Rating:

4-Extreme	Health: 1
3-High	Flammability: 1
2-Moderate	Instability: 0
1-Slight	Special:
0-Insignificant	

Special Fire Fighting Procedures:

FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. EXTINGUISHING MEDIA SHOULD BE CHOSEN BASED ON THE NATURE OF THE SURROUNDING FIRE. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY TO PREVENT BURSTING.

MATERIAL SAFETY DATA SHEET: DROP DEAD II AEROSOL

Unusual Fire and Explosion Hazards:

FIRE FIGHTING SHOULD BE DONE FROM UPWIND TO MINIMIZE POSSIBILITY OF EXPOSURE TO PESTICIDE, SMOKE, AND FUMES. EVACUATE PEOPLE DOWNWIND AS APPROPRIATE. AEROSOL CANS CAN EXPLODE WHEN HEATED. FLAME EXTENSION IS 0 INCHES, BURNBACK IS 0 INCHES. USE CARE AS SPILLS MAY BE SLIPPERY.

Section V - Health and Hazard Data

Threshold Limit Value:

NOT ESTABLISHED FOR MIXTURE. SEE SECTION II.

Effects of Overexposure:

Acute: (Short Term Exposure)

EYE CONTACT: CAUSES IRRITATION SEEN AS STINGING, TEARING, AND REDNESS. SKIN CONTACT: MAY CAUSE IRRITATION SEEN AS ITCHING AND REDNESS. PROLONGED OR REPEATED CONTACT AS FROM CLOTHING WET WITH MATERIAL MAY CAUSE DRYING, DEFATTING, AND CRACKING OF THE SKIN. INJECTION UNDER THE SKIN, IN MUSCLE, OR INTO THE BLOOD STREAM CAN CAUSE IRRITATION, INFLAMMATION, SWELLING, FEVER, AND SYSTEMIC EFFECTS, AND MILD CENTRAL NERVOUS SYSTEM DEPRESSION. INJECTION OF PRESSURIZED HYDROCARBONS CAN CAUSE SEVERE, PERMANENT TISSUE DAMAGE. INITIAL SYMPTOMS MAY BE MINOR. INHALATION: CAUSES RESPIRATORY IRRITATION SEEN AS COUGHING AND SNEEZING. AT LOW VAPOR CONCENTRATIONS, NO HARMFUL EFFECTS ARE EXPECTED. AT HIGH VAPOR CONCENTRATIONS, INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS HEADACHE, DIZZINESS, DROWSINESS, WEAKNESS, UNCONCIOUSNESS, POSSIBLE ANESTHETIC EFFECTS FROM CENTRAL NERVOUS SYSTEM DEPRESSION, AND MAY BE FATAL. INGESTION: MAY CAUSE IRRITATION WITH POSSIBLE NAUSEA, VOMITING, AND DIARRHEA.

Chronic: (Long Term Exposure)

ON RARE OCCASIONS, PROLONGED AND REPEATED EXPOSURE TO HYDROCARBON MIST POSES A RISK OF CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGHING ARE THE MOST COMMON SYMPTOMS. ASPIRATION MAY LEAD TO PULMONARY EDEMA AND HEMORRHAGE AND MAY BE FATAL. SIGNS OF LUNG INVOLVEMENT INCLUDE INCREASED RESPIRATION AND HEART RATES AS WELL AS A BLUISH DISCOLORATION OF THE SKIN. CHRONIC SKIN CONTACT MAY PROMOTE DERMATITIS AND OIL ACNE. IN RARER CASES, AN INCREASED SENSITIVITY TO SUNLIGHT (PHOTOSENSITIVITY) MAY OCCUR. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ARE PRE-EXISTING RESPIRATORY AND SKIN CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, AND DERMATITIS. TARGET ORGANS: CENTRAL NERVOUS SYSTEM. THE PRIMARY ROUTES OF EXPOSURE ARE SKIN AND EYE CONTACT.

Primary Routes of Entry

☒ Inhalation ☐ Ingestion ☐ Absorption

Emergency First Aid Procedures:

Inhalation:

REMOVE VICTIM TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. GET MEDICAL ATTENTION.

Eye Contact:

RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING WITH PLENTY OF WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

Skin Contact:

WASH AFFECTED AREAS WITH PLENTY OF SOAP AND WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

Ingestion:

GIVE 3 TO 4 GLASSES OF WATER, BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. SEEK MEDICAL ATTENTION IF DISCOMFORT OCCURS.

Notes to Physician:

THERE IS NO SPECIFIC ANTIDOTE. TREAT THE PATIENT SYMPTOMATICALLY. IN THE EVENT OF INJECTION IN UNDERLYING TISSUE, IMMEDIATE TREATMENT SHOULD INCLUDE EXTENSIVE INCISION, DEBRIDEMENT AND SALINE IRRIGATION. INADEQUATE TREATMENT CAN RESULT IN ISCHEMIA AND GANGRENE. EARLY SYMPTOMS MAY BE MINIMAL.

Section VI - Toxicity Information

Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By:

☐ IARC ☐ NTP ☐ OSHA ☐ ACGIH ☐ Other

VOC CONTENT: 14.5% BY WEIGHT

SYNTHETIC ISOPARAFFINIC HYDROCARBON (<3% DMSO EXTRACTABLES)

IHL-RAT LC50: >290 PPM 3.

ORL-RAT LD50: >10 G/KG 3.

SKN-RBT LD50: >3 G/KG 3.

SKN SENSITIZER: NO 3.

MATERIAL SAFETY DATA SHEET: DROP DEAD II AEROSOL

SKN IRRITATION: SLIGHT 3.
EYE IRRITATION: SLIGHT 3.

THIS HYDROCARBON WAS ADMINISTERED ORALLY 5 DAYS/WEEK TO MALE AND FEMALE RATS AT 100, 500, OR 1000 MG/KG FOR 13 WEEKS. AN ADDITIONAL GROUP WAS DOSED WITH 100 MG/KG FOR 13 WEEKS FOLLOWED BY A 4-WEEK RECOVERY PERIOD. NO MORTALITIES OR CLINICAL EFFECTS WERE OBSERVED. LIVER AND KIDNEY WEIGHTS FOR THE 500 AND 1000 MG/KG EXPOSURE GROUPS WERE SIGNIFICANTLY INCREASED. AFTER THE 4-WEEK RECOVERY PERIOD, THERE WERE NO DIFFERENCES IN ORGAN WEIGHTS. 3.

HYDROCARBON MISTS DERIVED FROM PETROLEUM DISTILLATES ARE REPORTED TO HAVE LOW ACUTE AND SUB-ACUTE TOXICITIES IN ANIMALS. EFFECTS FROM SINGLE AND SHORT-TERM REPEATED EXPOSURES TO HIGH CONCENTRATIONS WELL ABOVE APPLICABLE WORKPLACE EXPOSURE LEVELS INCLUDE LUNG INFLAMMATORY REACTION, LIPOID GRANULOMA FORMATION, AND LIPOID PNEUMONIA. IN ACUTE AND SUB-ACUTE STUDIES INVOLVING EXPOSURES TO LOWER CONCENTRATIONS AT OR NEAR CURRENT WORK PLACE EXPOSURE LEVELS PRODUCED NO SIGNIFICANT TOXICOLOGICAL EFFECTS. IN LONG TERM STUDIES (UP TO TWO YEARS) NO CARCINOGENIC EFFECTS HAVE BEEN REPORTED IN ANY ANIMAL SPECIES TESTED. THESE PETROLEUM DISTILLATES ARE SEVERELY HYDROTREATED, SEVERELY SOLVENT EXTRACTED, AND/OR PROCESSED BY MILD HYDROTREATMENT AND EXTRACTION. FOR THIS REASON, THEY ARE NOT CLASSIFIED AS CANCER HAZARDS. 3.

PROPANE
IHL-LC50 >40% BY VOLUME 3.

ISOBUTANE
IHL-RAT LC50: 57 PPH/15M 4.

NO APPARANT ILL EFFECTS IN BREATHING CONCENTRATIONS OF 5% FOR 2 HOURS. 3.
CAUSES DROWSINESS IN SHORT TIME IN CONCENTRATIONS OF 1%. 3.

Section VII - Reactivity Data

Stability

☒ Stable ☐ Unstable

Conditions to Avoid:

KEEP AWAY FROM EXCESSIVE HEAT, HOT SURFACES, SPARKS, OPEN FLAME, AND ANY SOURCE OF IGNITION. EXPOSURE TO TEMPERATURES ABOVE 130° F/64° C MAY CAUSE BURSTING.

Hazardous Polymerization

☒ Will not occur ☐ May occur

Conditions to Avoid:

N/A

Incompatibility (Materials to Avoid):

STRONG OXIDIZING AGENTS SUCH AS CHLORINE BLEACH AND CONCENTRATED HYDROGEN PEROXIDE; ACIDS AND BASES.

Hazardous Decomposition Products:

OXIDES OF CARBON.

Section VIII - Spill Or Leak Procedures

Steps to be Taken if Material is Released or Spilled:

DUE TO THE NATURE OF THE AEROSOL PACKAGING, A LARGE SPILL IS UNLIKELY. FOR A SMALL SPILL, ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. WEAR APPROPRIATE PROTECTIVE CLOTHING. PREVENT PRODUCT FROM CONTAMINATING SOIL OR FROM ENTERING SEWAGE AND DRAINAGE SYSTEMS AND BODIES OF WATER.

Waste Disposal Method(s):

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS. IF RECYCLING IS NOT AVAILABLE, WRAP THE CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISPOSE OF IN TRASH. DO NOT INCINERATE OR PUNCTURE.

Neutralizing Agent:

N/A

Section IX - Special Protection Information

Required Ventilation:

LOCAL VENTILATION IS RECOMMENDED TO CONTROL EXPOSURE FROM OPERATIONS THAT CAN GENERATE EXCESSIVE LEVELS OF MISTS OR VAPORS. LOCAL VENTILATION IS PREFERRED, BECAUSE IT PREVENTS DISPERSION INTO WORK AREAS BY CONTROLLING IT AT ITS SOURCE.

Respiratory Protection:

RESPIRATORS SHOULD BE SELECTED BY AND USED UNDER THE DIRECTION OF A TRAINED HEALTH AND SAFETY PROFESSIONAL FOLLOWING REQUIREMENTS FOUND IN OSHA'S RESPIRATOR STANDARD (29 CFR 1910.134) AND ANSI'S STANDARD FOR RESPIRATORY PROTECTION (Z88.2-1992). FOR CONCENTRATIONS ABOVE THE TLV AND/OR PEL BUT LESS THAN 10 TIMES THESE LIMITS, A NIOSH APPROVED HALF-FACEPIECE RESPIRATOR EQUIPPED WITH APPROPRIATE CHEMICAL CARTRIDGES MAY BE USED. FOR CONCENTRATIONS GREATER THAN 10 TIMES THE TLV AND/OR PEL, CONSULT THE NIOSH RESPIRATOR DECISION LOGIC FOUND

MATERIAL SAFETY DATA SHEET: DROP DEAD II AEROSOL

IN PUBLICATION NO. 87-116 OR ANSI Z88.2-1992.

Glove Protection:

NEOPRENE OR NITRILE RUBBER GLOVES IF REPEATED OR PROLONGED SKIN CONTACT IS LIKELY. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR HAND PROTECTION, 29 CFR 1910.138.

Eye Protection:

SAFETY GLASSES WITH SIDE SHIELDS IF THE METHOD OF APPLICATION PRESENTS THE LIKELIHOOD OF EYE CONTACT. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR EYE AND FACE PROTECTION, 29 CFR 1910.133.

Other Protection:

WEAR GENERAL-DUTY WORK CLOTHES AND SHOES. REMOVE SOAKED CLOTHING AND SHOES. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE. A SAFETY SHOWER AND AN EYEWASH STATION SHOULD BE AVAILABLE.

Section X - Storage and Handling Information

Storage Temperature

Max: 120°F Min: 30°F

Storage Conditions

☒ Indoors ☐ Outdoors ☐ Heated ☐ Refrigerated

Precautions to be Taken in Handling and Storing:

STORE IN A COOL, DRY AREA. DO NOT TRANSPORT OR STORE BELOW 32°F/0°C. DO NOT ALLOW PESTICIDE TO CONTAMINATE FOOD, FEED, OR NATURAL BODIES OF WATER. USE WITH CAUTION AROUND HEAT, SPARKS, PILOT LIGHTS, STATIC ELECTRICITY AND OPEN FLAME. CONTENTS UNDER PRESSURE.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN. READ THE ENTIRE LABEL BEFORE USING THE PRODUCT. FOLLOW THE LABEL DIRECTIONS. DO NOT APPLY THIS PRODUCT TO ENERGIZED ELECTRICAL EQUIPMENT.

Section XI - Regulatory Information

Chemical Name

None.

CAS Number

Upper % Limit

Those Ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Please call 1-800-527-9919 for additional information if you are a California customer. This MSDS is not intended for users in the state of California.

Section XII - References

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE INDICES, ACGIH, 2006.
2. OSHA PEL.
3. VENDOR'S MSDS.
4. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES, CCINFOWeb, 2006.

ALL THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE TOXIC SUBSTANCES CONTROL ACT (TSCA) AND ARE EITHER LISTED ON THE TSCA INVENTORY OR OTHERWISE EXEMPTED FROM LISTING.

IRR:IRRITANT, FLAM/FLAMM:FLAMMABLE, COMB:COMBUSTIBLE, CORR:CORROSIVE CARC:CARCINOGENIC, TOX:TOXIC, N/A:NOT APPLICABLE, N/E:NOT ESTABLISHED, COC:CLEVELAND OPEN CUP, PMCC:PENSKY-MARTIN CLOSED CUP, TCC:TAGLIABUE CLOSED CUP, LEL:LOWER EXPLOSION LIMIT, UEL:UPPER EXPLOSION LIMIT, NFPA:NATIONAL FIRE PROTECTION ASSOCIATION, IARC:INTERNATIONAL AGENCY FOR THE RESEARCH ON CANCER, NTP:NATIONAL TOXICOLOGY PROGRAM, OSHA:OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION, ACGIH:AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS, TLV:THRESHOLD LIMIT VALUE, PEL:PERMISSIBLE EXPOSURE LIMIT, STEL:SHORT-TERM EXPOSURE LIMIT, MLD:MILD, MOD:MODERATE, SEV:SEVERE, MUT:MUTAGENIC, ASPHYX:ASPHYXIAN, PNOS:PARTICLES (INSOLUBLE) NOT OTHERWISE SPECIFIED, PNOR:PARTICULATES NOT OTHERWISE REGULATED, SDT:STANDARD DRAIZE TEST, ORL:ORAL, IHL:INHALATION, HMN:HUMAN

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage, or disposal of the product.

©2007 [NCH Corporation](#) All rights reserved.