


Hale Street
 Northampton, MA 01950
 100-US STAIN
 Tel. (978) 462-2720

Samuel Cabot Inc.



33360 Central Avenue
 Union City, CA 94587
 Tel. 888-WC STAIN
 Fax. (510) 477-9615

FM
 MUPD
 Compliance

Material Safety Data Sheet

IDENTIFICATION (As Used on Label and List) 3457, 3458, 3459 Australian Timber Oil

Section I

Emergency Telephone Number Call local emergency medical services.
 Call Chem-Tel 1-800-255-3924.

Prepared October 2000 Signature of Preparer (Optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS #	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (Optional)
Stearic Acid Distillates (MSL*)	8052-41-3	100 ppm TWA	100 ppm TWA		

These products contain a Maximum Volatile Organic Compound (V.O.C.) content of 550 grams per liter (4.6 pounds per gallon).

MSL - Massachusetts Substance List

Section III - Physical/Chemical Characteristics

Boiling Point	> 300°F	Specific Gravity (H2O = 1)	0.86
Vapor Pressure (mm Hg.)	@ 68°F < 5mm Hg	Melting Point	Not applicable
Density (AIR = 1)	> 1	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water	Negligible		
Appearance and Odor	Colored liquids - solvent odor		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	> 100°F (TCC)	Flammable Limits	LEL 1.0	UEL 6.0
---------------------------	---------------	------------------	---------	---------

Extinguishing Media Water fog, foam, dry chemical, CO₂, Class B fire extinguishers.

Special Fire Fighting Procedures

Do not use a direct water stream. Recommend self-contained breathing apparatus for firefighters. Water may be used to cool closed containers. Moderate Fire Hazard.

Special Fire and Explosion Hazards

Is a flammable liquid. Closed containers may explode when exposed to extreme heats. Combustion may produce hazardous gases. Danger: - Rags, steel wool, lambs wool or waste soaked with Australian Timber Oil may spontaneously catch fire if improperly stored. Immediately after each use, place rags, steel wool, lambs wool or waste in a sealed, water-filled metal container.

Section V - Reactivity Data

Stability	Unstable	Conditions to Avoid	Storage near heat, sparks, flame, electrical equipment & other ignition sources.
	Stable X		
Incompatibility (Materials to Avoid)			Avoid contact with strong oxidizing agents.
Hazardous Decomposition or Byproducts			Fumes, smoke, carbon dioxide, carbon monoxide, various hydrocarbons.
Hazardous Polymerization	May Occur X	Conditions to Avoid	Soak oily rags and cloths in water after use to avoid spontaneous combustion.
	Will Not Occur		

Section VI - Health Hazard Data

Routes of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic)	May be irritating to eyes, skin, nose, throat; chronic dryness and dermatitis to skin. Acute and chronic inhalation may cause headaches, dizziness, nausea, fatigue. Ingestion may cause irritation and vomiting.		
Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? No
Signs and Symptoms of Exposure	Irritation to eyes, skin, respiratory tract. Headaches, dizziness, nausea, fatigue.		
Medical Conditions Generally Aggravated by Exposure	Persons with breathing difficulties, skin sensitivities, eye sensitivities.		
Emergency and First Aid Procedures	EYES: Flush with water for 15 minutes. Call physician. SKIN: Wash affected areas with soap and water. Remove contaminated clothing. INHALATION: Remove to fresh air. Restore normal breathing. INGESTION: Do not induce vomiting. Drink plenty of milk or water. Call physician immediately.		

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled
 Remove ignition sources. Ventilate area. Dike and contain spill with inert material (i.e. sand, earth). Add absorbent material and remove to closed containers for disposal. Wear protective clothing.

Waste Disposal Method
 Incinerate and/or dispose of in accordance with local, state, and federal regulations.

Precautions to be Taken in Handling and Storing
 Do not use or store near heat, possible ignition sources, or food products. Keep containers closed when not in use. Keep away from children and animals.

Section VIII - Control Measures

Respiratory Protection (Specify Type)	Use approved vapor/mist respirator in areas of poor ventilation.		
Ventilation	Local Exhaust	In areas of poor ventilation	Special None known Other None known
	Mechanical (General)	If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.	
Protective Gloves	Neoprene or rubber gloves if necessary.		Eye Protection
			Splash proof safety goggles or glasses.
Other Protective Clothing or Equipment	Wear a vapor/mist respirator during spray applications.		
Work Hygienic Practices	Read label on can before using. Do not reuse empty containers. Not intended for interior surfaces. For exterior use only. Furniture coated with Australian Timber Oil may be stored indoors.		